

SUJETACABLES CINCADO DIN 741

ZINC PLATED WIRE ROPE CLIP DIN 741

FICHA TÉCNICA

TECHNICAL DATA SHEET

Material / Material:

Cuerpo: Hierro fundido, Estribo: Acero
Body: Cast Iron, U-bolt: Steel

Recubrimiento / Coating:

Cincado
Zinc plated

Pasivado / Passivated:



Azul
Blue

Micraje / Microns:

6 µ
6 µ

Corrosión / Corrosion:

Óxido blanco - 6h C.N.S. Óxido rojo - 72h C.N.S.
White oxide - 6h C.N.S. Red oxide - 72h C.N.S.



CÓDIGO Code / Code	MEDIDA Measure / Mesure	CABLE Wire rope / Câble	A	B	C	D	I	L	L1	PESO Weight / Poids
	m.m.	m.m.	m.m.	m.m.	m.m.	m.m.	m.m.	m.m.	m.m.	Kg.
741Z03	3	3	21	10	10	M 4	9	20	12	0,01
741Z05	5	5	24	11	10	M 5	11	24	13	0,02
741Z06	6	6,5	26	12	11	M 5	13	28	15	0,02
741Z08	8	8	30	14	15	M 6	16	34	19	0,02
741Z10	10	10	37	20	19	M 8	20	42	22	0,06
741Z12	12	13	44	25	23	M10	25	55	30	0,11
741Z14	14	14	46	25	25	M10	27	57	30	0,12
741Z16	16	16	52	28	28	M12	30	63	33	0,15
741Z20	20	19	58	32	34	M12	34	75	38	0,23
741Z22	22	22	64	35	35	M14	38	85	44	0,27
741Z26	26	26	68	38	38	M14	42	95	45	0,30
741Z30	30	30	80	40	45	M16	50	110	50	0,50
741Z32	32	32	80	40	45	M16	50	118	50	0,65
741Z34	34	34	88	45	52	M16	54	120	55	0,68
741Z40	40	40	95	48	58	M16	60	140	60	0,86

Uso

El sujetacable, compuesto por una horquilla y un cuerpo puente, permite hacer gazas de cables o conexiones donde no se pueda prensar ni usar terminales o uniones temporales de cables, por consiguiente no precisa de carga máxima de soporte.

Aplicación

Para verificar que el sujetacable mantiene el apriete inicial, tras la primera tracción del cable comprobaremos que no exista pérdida de apriete y, si fuera necesario, lo corregiremos.

Use

The cable clamp, made up of a fork and a bridge body, allows cable loops or connections to be made where it is not possible to press or use terminals or temporary cable connections, therefore it does not require a maximum support load.

Application

To verify that the cable clamp maintains the initial tightness, after the first cable pull we will check that there is no loss of tightness and, if necessary, we will correct it.