

TORNILLO AUTORROSCANTE PARA HORMIGÓN DE ACERO CEMENTADO

CONCRETE SELF-TAPPING SCREW - HARDENED STEEL
 VIS AUTOTARAUSE EN ACIER CÉMENTE POUR BÉTON
 BETONBLECHSCHRAUBE EINSATZGEHÄRTET



CAJA / BOX / BOÎTE

ACERO CEMENTADO / HARD. STEEL

CÓDIGO <i>Code / Code</i>	MEDIDA <i>Measure / Mesure</i> ØxL m.m.	LLAVE <i>Wrench / Clé</i> S	t _{fix} ⁽¹⁾ m.m. ≤	DK m.m.	K m.m.	t _{inst} Nm	hc ⁽²⁾ m.m.	
HO7665032	6,5x32	8	2	11,3	5	12	30	500
HO7665045	6,5x45	8	15	11,3	5	12	30	500
HO7665057	6,5x57	8	27	11,3	5	12	30	500
HO7665070	6,5x70	8	40	11,3	5	12	30	500
HO7665080	6,5x80	8	50	11,3	5	12	30	250
HO7665100	6,5x100	8	70	11,3	5	12	30	250
HO7665125	6,5x125	8	95	11,3	5	12	30	250

⁽¹⁾ t_{fix}: Grosor máximo a fijar / *Maximum thickness to fix* / Épaisseur maximale à fixer
⁽²⁾ hc: Profundidad de instalación / *Installation depth*

TORNILLO AUTORROSCANTE PARA HORMIGÓN DE ACERO CEMENTADO + EPDM Ø19

CONCRETE SELF-TAPPING SCREW WITH EPDM WASHER - HARDENED STEEL
 VIS AUTOTARAUSE EN ACIER CÉMENTE POUR BÉTON AVEC RONDELLE EPDM
 BETONBLECHSCHRAUBE EINSATZGEHÄRTET MIT SCHEIBE EPDM



CAJA / BOX / BOÎTE

ACERO CEMENTADO / HARD. STEEL

CÓDIGO <i>Code / Code</i>	MEDIDA <i>Measure / Mesure</i> ØxL m.m.	LLAVE <i>Wrench / Clé</i> S	t _{fix} ⁽¹⁾ m.m. ≤	DK m.m.	K m.m.	t _{inst} Nm	hc ⁽²⁾ m.m.	
HO76A1965032	6,5x32	8	2	11,3	5	12	30	1.000
HO76A1965045	6,5x45	8	15	11,3	5	12	30	500
HO76A1965057	6,5x57	8	27	11,3	5	12	30	500
HO76A1965070	6,5x70	8	40	11,3	5	12	30	500
HO76A1965080	6,5x80	8	50	11,3	5	12	30	250
HO76A1965100	6,5x100	8	70	11,3	5	12	30	250
HO76A1965125	6,5x125	8	95	11,3	5	12	30	250

⁽¹⁾ t_{fix}: Grosor máximo a fijar / *Maximum thickness to fix* / Épaisseur maximale à fixer
⁽²⁾ hc: Profundidad de instalación / *Installation depth*

CARACTERÍSTICAS Y VENTAJAS

- Tornillo con cabeza hexagonal y ranura
- Punta de diamante
- Rosca especial high-low de 60°/40° estriada
- Se rosca directamente sobre hormigón, cemento, ladrillos y bloques huecos.
- Ahorra una operación al suprimir el taco.
- Colocación rápida y sencilla.
- Requiere taladro previo de 5mm.
- Permite la fijación cerca de las aristas.
- No afecta al pretensado de la viga de hormigón.
- Fijación desmontable y segura.
- Fijación de chapas simples y de paneles prefabricados sobre estructuras de hormigón.
- Recubrimiento azul anticorrosión que resiste 1.000 horas en C.N.S.

CHARACTERISTICS AND ADVANTAGES

- Screw with hexagonal head and slot
- Diamond tip
- Special high-low 60°/40° grooved thread
- Threads directly into concrete, cement, bricks and hollow blocks.
- Saves an operation by suppressing the taco.
- Quick and easy placement.
- Requires previous drilling of 5mm.
- Allows fixing near the edges.
- Does not affect the prestressing of the concrete beam.
- Detachable and safe fixing.
- Fastening of simple plates and prefabricated panels on concrete structures.
- Blue anti-corrosion coating that resists 1,000 hours in S.F.C.

INSTALACIÓN / INSTALLATION

