

TORNILLO DIRECTO HORMIGÓN

 DIRECT FIXING SCREW FOR CONCRETE
 VIS DE FIXATION DIRECTE POUR LE BÉTON
 GERADE-BETONSCHRAUBE



CAJA / BOX / BOÎTE 

CÓDIGO Code / Code	MEDIDA Measure / Mesure ØxL m.m.	Ø BROCA Drill Ø / Ø Foret D m.m.	GROSOR A FIJAR Thickness to fix / Épaisseur tfix m.m.	LLAVE Wrench / Clé TX	*CC.		PROF. TALADRO Hole depth / Prof. trou h1 m.m.	CINCADO / ZINC PLATED	
					Extracción tension load / extraction	Cizallado shear load / cisaillement			
					kN	kN			
TH075050	7,5x50	6	10	T-30	6,00	7,58	65	100	1.000
TH075080	7,5x80	6	40	T-30	6,00	7,58	65	100	1.000
TH075090	7,5x90	6	50	T-30	6,00	7,58	65	100	1.000
TH075100	7,5x100	6	60	T-30	6,00	7,58	65	100	1.000
TH075120	7,5x120	6	80	T-30	6,00	7,58	65	100	500
TH075135	7,5x135	6	95	T-30	6,00	7,58	65	100	500
TH075150	7,5x150	6	110	T-30	6,00	7,58	65	100	500
TH075180	7,5x180	6	140	T-30	6,00	7,58	65	100	500

AUTOSERVICIO / SELF-SERVICE / AUTO-SERVICE 

CÓDIGO Code / Code	MEDIDA Measure / Mesure MxL m.m.	CINCADO / ZINC PLATED	
			
BFTH075050	7,5x50	14	12
BFTH075080	7,5x80	14	12
BFTH075090	7,5x90	12	12
BFTH075100	7,5x100	12	12

PEDIDO MÍNIMO 1 EMBALAJE / MINIMUM ORDER 1 PACKAGING
 COMMANDE MINIMALE 1 EMBALLAGE / MINDESTBESTELLMENGE 1 VERPACKUNG

TORNILLO DIRECTO HORMIGÓN C/PEQUEÑA

 DIRECT FIXING SCREW RED. HEAD FOR CONCRETE
 VIS DE FIXATION DIRECTE TÊTE RÉDUIT POUR LE BÉTON
 GERADE-BETONSCHRAUBE MIT ZYLINDERKOPF



CAJA / BOX / BOÎTE 

CÓDIGO Code / Code	MEDIDA Measure / Mesure ØxL m.m.	Ø BROCA Drill Ø / Ø Foret D m.m.	GROSOR A FIJAR Thickness to fix / Épaisseur tfix m.m.	LLAVE Wrench / Clé TX	*CC.		PROF. TALADRO Hole depth / Prof. trou h1 m.m.	CINCADO / ZINC PLATED	
					Extracción tension load / extraction	Cizallado shear load / cisaillement			
					kN	kN			
THCP75080	7,5x80	6	40	T-30	6,00	7,58	65	100	1.000
THCP75090	7,5x90	6	50	T-30	6,00	7,58	65	100	1.000
THCP75100	7,5x100	6	60	T-30	6,00	7,58	65	100	1.000
THCP75120	7,5x120	6	80	T-30	6,00	7,58	65	100	500
THCP75135	7,5x135	6	95	T-30	6,00	7,58	65	100	500
THCP75150	7,5x150	6	110	T-30	6,00	7,58	65	100	500
THCP75180	7,5x180	6	140	T-30	6,00	7,58	65	100	500

INFORMACIÓN TÉCNICA / TECHNICAL INFORMATION

